

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 43370 - AUTOGEAR OIL SYN LS 75W-140
Product code : 43370

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

77 Lubricants
1761 JA - The Netherlands
T +31 (0)78 6527652
technical@77lubricants.nl - www.77lubricants.nl

1.4. Emergency telephone number

Emergency number : +31 (0)78 6527652
Monday to Friday: 09:00 - 16:00 (CET)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) : Warning

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous ingredients	: Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl; Polysulphides, di-tert-Bu
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction.
Precautionary statements (CLP)	: P261 - Avoid breathing dust, fume, gas, mist, spray, vapours. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

Other hazards not contributing to the classification	: Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.
--	---

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	25 – 50	Not classified
Polysulphides, di-tert-Bu	(CAS-No.) 68937-96-2 (EC-No.) 273-103-3 (REACH-no) 01-2119540515-43	1 – 5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	1 – 2,5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] substance with a Community workplace exposure limit (Note L)	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6 (REACH-no) 01-2119471299-27	1 – 2,5	Not classified
O,O,O-triphenyl phosphorothioate	(CAS-No.) 597-82-0 (EC-No.) 209-909-9 (REACH-no) 01-2119979545-21	0,1 – 0,5	Repr. 2, H361fd Aquatic Chronic 4, H413

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	(EC-No.) 931-384-6 (REACH-no) 01-2119493620-38	(9,4 ≤C < 100) Skin Sens. 1, H317 (50 ≤C < 100) Eye Dam. 1, H318

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear. May cause an allergic skin reaction.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Eliminate all ignition sources if safe to do so.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, spray, vapours. Wear personal protective equipment.
Handling temperature : < 40 °C
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage temperature : 50 °C
Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	5 mg/m ³
--------------------------------	---------------------

Belgium - Occupational Exposure Limits

Limit value (mg/m ³)	5 mg/m ³
----------------------------------	---------------------

Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m ³)	5 mg/m ³
------------------------------	---------------------

Croatia - Occupational Exposure Limits

GVI (granična vrijednost izloženosti) (mg/m ³)	5 mg/m ³
--	---------------------

Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m ³)	5 mg/m ³
---	---------------------

Expoziční limity (NPK-P) (mg/m ³)	10 mg/m ³
---	----------------------

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Denmark - Occupational Exposure Limits	
Grænsevædi (8 timer) (mg/m ³)	1
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m ³)	5 mg/m ³
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH STEL (mg/m ³)	10 mg/m ³

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	5

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
EU - Occupational Exposure Limits	
IOELV TWA (mg/m ³)	5 mg/m ³
IOELV STEL (mg/m ³)	10 mg/m ³
Bulgaria - Occupational Exposure Limits	
OEL TWA (mg/m ³)	5 mg/m ³
OEL STEL (mg/m ³)	10 mg/m ³
Croatia - Occupational Exposure Limits	
GVI (granična vrijednost izloženosti) (mg/m ³)	5 mg/m ³
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	10 mg/m ³
Czech Republic - Occupational Exposure Limits	
Expoziční limity (PEL) (mg/m ³)	5 mg/m ³
Expoziční limity (NPK-P) (mg/m ³)	10 mg/m ³
Denmark - Occupational Exposure Limits	
Grænsevædi (8 timer) (mg/m ³)	1 mg/m ³
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m ³)	5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid.

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:					
Breakthrough time : refer to the recommendations of the supplier					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection:

Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. EN 166

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -36
Boiling point	: No data available
Flash point	: > 201 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 879 kg/m ³ @15°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 174 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5,53 mg/l/4h

O,O,O-triphenyl phosphorothioate (597-82-0)

LD50 oral (rat)	> 10000 mg/kg bodyweight
LD50 dermal (rat)	> 2000 mg/kg bodyweight

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

LD50 oral (rat)	2000 mg/kg bodyweight
-----------------	-----------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

NOAEL (subacute, oral, animal/male, 28 days)	500 mg/kg bodyweight
--	----------------------

NOAEL (subacute, oral, animal/female, 28 days)	150 mg/kg bodyweight
--	----------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight
-------------------------------------	-------------------------

Aspiration hazard : Not classified

43370 - AUTOGEAR OIL SYN LS 75W-140

Viscosity, kinematic	174 mm ² /s @40°C
----------------------	------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	> 100 mg/l Pimephales promelas
-------------	--------------------------------

EC50 Daphnia 1	> 10000 mg/l Daphnia magna
----------------	----------------------------

NOEC chronic fish	10 mg/l Oncorhynchus mykiss
-------------------	-----------------------------

NOEC chronic crustacea	10 mg/l Daphnia magna
------------------------	-----------------------

NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata
--------------------	--

O,O,O-triphenyl phosphorothioate (597-82-0)

LC50 fish 1	> 100 mg/l Danio rerio
-------------	------------------------

EC50 Daphnia 1	> 100 mg/l Daphnia magna
----------------	--------------------------

EC50 72h algae (1)	> 100 mg/l Desmodesmus subspicatus
--------------------	------------------------------------

NOEC chronic crustacea	> 5,5 mg/l 21 DY Daphnia Magna
------------------------	--------------------------------

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Polysulphides, di-tert-Bu (68937-96-2)

EC50 Daphnia 1	63 mg/l Daphnia Magna
EC50 72h algae (1)	> 100 mg/l

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

LC50 fish 1	24 mg/l
EC50 Daphnia 1	91,4 mg/l
EC50 96h algae (1)	6,4 mg/l
NOEC (chronic)	0,12 mg/l
NOEC chronic fish	3,2 mg/l
NOEC chronic crustacea	0,66 mg/l
NOEC chronic algae	1,7 mg/l

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h algae (1)	3 mg/l

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

O,O,O-triphenyl phosphorothioate (597-82-0)

Biodegradation	18,55 (17,8 – 19,3) %
----------------	-----------------------

Polysulphides, di-tert-Bu (68937-96-2)

Biodegradation	13 % 28 DAYS OECD TG 301 B
----------------	----------------------------

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

Persistence and degradability	Not biodegradable.
Biodegradation	7,4 % 28 DY, OECD TG 301 B

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Persistence and degradability	Not biodegradable.
Biodegradation	31 % 28 d OECD 301F

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

O,O,O-triphenyl phosphorothioate (597-82-0)

Bioconcentration factor (BCF REACH)	2551
-------------------------------------	------

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

Polysulphides, di-tert-Bu (68937-96-2)

Partition coefficient n-octanol/water (Log Kow)	5,6
---	-----

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

Partition coefficient n-octanol/water (Log Kow)	9,4
---	-----

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9,2
---	-----

12.4. Mobility in soil

O,O,O-triphenyl phosphorothioate (597-82-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR	
Transport hazard class(es) (ADR)	: Not applicable
IMDG	
Transport hazard class(es) (IMDG)	: Not applicable
IATA	
Transport hazard class(es) (IATA)	: Not applicable
ADN	
Transport hazard class(es) (ADN)	: Not applicable
RID	
Transport hazard class(es) (RID)	: Not applicable

14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

Germany

- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- Ministry's list of carcinogens : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Polysulphides, di-tert-Bu, Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

- Ministry's list of mutagens : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Polysulphides, di-tert-Bu, Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] are listed

- NON-exhaustive list of reproductive toxins - Breastfeeding : None of the components are listed

- NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed

- NON-exhaustive list of reproductive toxins - Evolution : None of the components are listed

Denmark

- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Supersedes	Added	
	Revision date	Added	
2.1	Adverse physicochemical, human health and environmental effects	Removed	
2.2	Precautionary statements (CLP)	Modified	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after inhalation	Modified	
4.1	First-aid measures after ingestion	Modified	

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.1	First-aid measures after eye contact	Modified	
4.2	Symptoms/effects after skin contact	Modified	
4.2	Symptoms/effects after eye contact	Modified	
4.3	Other medical advice or treatment	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Modified	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Other information	Added	
6.3	Methods for cleaning up	Modified	
6.4	Reference to other sections (8, 13)	Modified	
7.1	Hygiene measures	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
8.2	Environmental exposure controls	Added	
8.2	Appropriate engineering controls	Added	
8.2	Eye protection	Modified	
9.1	Melting point	Added	
10.1	Reactivity	Added	
12.1	Ecology - general	Added	
13.1	Waste treatment methods	Added	
13.1	Waste disposal recommendations	Modified	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

43370 - AUTOGEAR OIL SYN LS 75W-140

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PNEC	Predicted No-Effect Concentration
PBT	Persistent Bioaccumulative Toxic
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Repr. 2	Reproductive toxicity, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness