

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : 42975 - MOTORCYCLE OIL SYN 4T 15W-50
UFI : RRP3-K7GJ-6008-PRAW
Product code : 42975
Type of product : Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Professional use, Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

77 Lubricants
1761 JA - The Netherlands
T +31 (0)78 6527652
technical@77lubricants.nl - www.77lubricants.nl

1.4. Emergency telephone number

Emergency number : +31 (0)78 6527652
Monday to Friday: 09:00 - 16:00 (CET)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (Note L)	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (EC Index-No.) 649-483-00-5 (REACH-no) 01-211947-4889	≥ 75	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (Note L)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	1 – 5	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (Note L)	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (EC Index-No.) 649-483-00-5 (REACH-no) 01-2119474889-13	1 – 5	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.] (Note L)	(CAS-No.) 72623-86-0 (EC-No.) 276-737-9 (EC Index-No.) 649-482-00-X (REACH-no) 01-2119474878-16	1 – 5	Asp. Tox. 1, H304

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage temperature : < 40 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

EU - Occupational Exposure Limits

IOELV TWA (mg/m³)	5 mg/m³
-------------------	---------

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

IOELV STEL (mg/m ³)	10 mg/m ³
---------------------------------	----------------------

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	5 mg/m ³
--------------------------------	---------------------

Belgium - Occupational Exposure Limits

Limit value [mg/m ³]	5 mg/m ³
Short time value [mg/m ³]	10 mg/m ³

Bulgaria - Occupational Exposure Limits

OEL TWA (mg/m ³)	5 mg/m ³
------------------------------	---------------------

Croatia - Occupational Exposure Limits

GVI (granična vrijednost izloženosti) (mg/m ³)	5 mg/m ³
--	---------------------

Czech Republic - Occupational Exposure Limits

Expoziční limity (PEL) (mg/m ³)	5 mg/m ³
Expoziční limity (NPK-P) (mg/m ³)	10 mg/m ³

Denmark - Occupational Exposure Limits

Grænseværdi (8 timer) (mg/m ³)	1
--	---

Netherlands - Occupational Exposure Limits

Grenswaarde TGG 8H (mg/m ³)	5 mg/m ³
---	---------------------

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH STEL (mg/m ³)	10 mg/m ³

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin and body protection:

Wear suitable protective clothing

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -33 °C
Boiling point	: No data available
Flash point	: > 201 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 875 kg/m ³ @15°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 126,5 mm ² /s @40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	0 mg/l/4h
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.] (72623-86-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5,53 mg/l/4h

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	≥ 5,53 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Not classified
-----------------------	------------------

STOT-single exposure	: Not classified
----------------------	------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

Aspiration hazard : Not classified

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Viscosity, kinematic	126,5 mm²/s @40°C
----------------------	-------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l Daphnia magna
EC50 72h algae (1)	> 100 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.] (72623-86-0)

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)

LC50 fish 1	> 100 mg/l
-------------	------------

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocabons.] (72623-86-0)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

12.4. Mobility in soil

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocabons.] (72623-86-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : 13 02 06* - synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK)

: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Ministry's list of carcinogens

: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] is listed

Ministry's list of mutagens

: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] is listed

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NON-exhaustive list of reproductive toxins - : None of the components are listed

Breastfeeding

NON-exhaustive list of reproductive toxins - Fertility : None of the components are listed

NON-exhaustive list of reproductive toxins - : None of the components are listed

Evolution

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

42975 - MOTORCYCLE OIL SYN 4T 15W-50

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:

Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness