



# UNIVERSAL TRACTOR OIL

## 85W

### Product Description:

**UNIVERSAL TRACTOR OIL 85W** is a high performance fluids for use in transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors.

**UNIVERSAL TRACTOR OIL 85W** is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Enhanced frictional properties optimize clutch performance and ensure noise free operation of wet brakes.
- High viscosity index coupled with high shear stability provides consistent performance.
- Excellent low temperature fluidity provides good response and effective lubrication at low ambient temperatures.
- Robust anti-wear and extreme pressure properties control wear, extend equipment life and reduce maintenance costs.
- Multipurpose capability reduces inventory and prevents accidental contamination and misapplication.

**UNIVERSAL TRACTOR OIL 85W** exceeds the following performance criteria:

**API GL-4**

**Case MS 1204/6/7/9**

**Volvo WB101**

**Eaton I-280-S**

**JD J20C**

**MF M1135/1143**

**Allison C4**

**Sauer Danfoss**

**Ford M2C86B/C**

**MF M1145**

**JCMAS HK P-041**

**Ford M2C 134D**

**Cat TO-2**

**Eaton M-2950S**



| Property              | Unit               | Test Method | Typical Value |
|-----------------------|--------------------|-------------|---------------|
| SAE Grade             |                    | SAE J306    | 85W           |
| Density@15°C          | kg/m <sup>3</sup>  | ASTM D4052  | 888.7         |
| Kin. Viscosity @40°C  | mm <sup>2</sup> /s | ASTM D7042  | 67.5          |
| Kin. Viscosity @100°C | mm <sup>2</sup> /s | ASTM D7042  | 11.2          |
| Viscosity Index       |                    | ASTM D2270  | 158           |
| Flash Point COC       | °C                 | ASTM D92    | >201          |
| Pour Point            | °C                 | ASTM D7346  | -39           |
| Total Base Number     | mgKOH/g            | ASTM D2896  | 9.7           |

**Product Nr:** 43310

**Date Superseded:** 16-12-2019

**Date Issued:** 4-4-2025

**Revision nr:** 06