



ATF L8S

Product Description:

ATF L8S is a synthetic high quality heavy-duty oil intended exclusively for ZF 6-speed and 8-speed automatic car transmissions. Subjected to extreme testing, **ATF L8S** guarantees maximum performance of the automatic transmission. At the same time, the wear of heavily loaded components is minimized due to the specifically matched oils.

ATF L8S is based on fully synthetic base in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Excellent lubrication, even under extreme conditions.
- Very high protection against wear, corrosion and foam.
- High "shear stable".
- Very low Pour point, can be used by very cold temperatures.
- High Viscosity Index.

ATF L8S exceeds the following performance criteria:

VW G 060 162	BMW 83 22 2 152 426	BMW83 22 2 305 397
BMW 83 22 2 289 720	VW G 055 540	ATF SP-IV-RR

ATF L8S is also suitable where the following specifications are required:

M 1375.4	VW G 055 005	Toyota Type WS	Nissan Matic S
Hyundai SP-IV		Mercon LV	Dexron VI
JWS 3324			



Property	Unit	Test Method	Typical Value
Color		Visual	Colorless to light Yellow
Density @15°C	kg/m ³	ASTM D4052	844
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	27.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.7
Brookfield Viscosity @-40°C	cP	ASTM D2983	9300
Viscosity Index		ASTM D2270	160
Flash Point COC	°C	ASTM D92	>201

Product Nr: 45040
Date Superseded: 20-02-2019

Date Issued: 16-12-2019
Revision nr: 04