



# ATF DX II

## Product Description:

**ATF DX II** is a high quality universal fluid to be used in automatic transmission, torque converters and power steering of passenger cars, light vans and commercial vehicles.

**ATF DX II** is formulated on high quality re-refined mineral and virgin synthetic base oil in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against corrosion, foam and wear.

**ATF DX II** meets the following performance criteria:

**GM Dexron II-D**  
**MAN 339 type Z1**  
**Voith H55.6335.xx**

**MAN 339 type V1**  
**MB 236.9**  
**ZF TE-ML 03D/04D/14A/17C**



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	855
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	35.9
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	7.3
Viscosity Index		ASTM D2270	175
Viscosity Brookfield @-40°, max	cP	ASTM D2983	50.000
Flash Point COC	°C	ASTM D92	172
Pour Point	°C	ASTM D7346	-48

**Product Nr:** 43200  
**Date Superseded:** 26-09-2018

**Date Issued:** 16-12-2019  
**Revision nr:** 04