



# EP GREASE

## NLGI 2

### Product Description:

**EP GREASE NLGI 2** is a high quality multipurpose lithium thickened EP-2 grease suited for automotive, agriculture and industrial applications.

**EP GREASE NLGI 2** is suitable for use in a wide range of plain and rolling bearings.

**EP GREASE NLGI 2** is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent resistance to humidity, preventing that moisture reaches the metal surfaces that need to be lubricated.
- High anti-corrosion, antioxidant and anti-rust capacity.
- High adhesion and smoothness.
- Excellent mechanical stability.

**Temp Range:** Continuous operation: -20°C to + 130°C. Short periods maximum +140°C

**EP GREASE NLGI 2** exceeds the following performance criteria.:

**KP2K-20**

**L-XCEB-2**

Property	Unit	Test Method	Typical Value
NLGI Grade		ASTM D217	2
Thickener type			Lithium
Color		Visual	Amber
Penetration loss after 105	mm	ASTM D217	10
Copper corrosion, 24h, 100 °C,		ASTM D4048	1B
Dropping Point	°C	IP 396	>190
Base Oil Viscosity @40°C	mm <sup>2</sup> /s	ISO 12058	220
4-Ball Weld Load	kg	ASTM D2596	>250
Water resistance, 3h, 90 °C		DIN 51807	1



**Product Nr:** 43990

**Date Superseded:** 25-09-2020

**Date Issued:** 8-10-2025

**Revision nr:** 4