

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 3454

Issue date: 28/08/2012 Revision date: 09/01/2024 Supersedes version of: 24/01/2022 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : 44880 - INDUSTRIAL SYSTEM OIL CL 150

Product code : 44880

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use,Professional use Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

77 Lubricants B.V. NL- 1761 JA The Netherlands T +31 (0)78 6527652

technical@77lubricants.nl - www.77lubricants.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P501 - Dispose of contents and container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	≥ 55 – < 75	Not classified
Residual oils (petroleum), solvent-dewaxed substance with national workplace exposure limit(s) (NL)	CAS-No.: 64742-62-7 EC-No.: 265-166-0 EC Index-No.: 649-471-00-X REACH-no: 01-2119480472- 38	≥ 25 – < 45	Not classified
Hydrocarbons, C10-C13, aromatics, <1% naphthalene substance with national workplace exposure limit(s) (AT, BE, CZ, DK, ES, GB, IE, LV, NL, RO, SE, CH); substance with a Community workplace exposure limit	EC-No.: 922-153-0 REACH-no: 01-2119451097- 39	< 0.3	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 (M=0)
N-Phenyl-1-naphthylamin substance with national workplace exposure limit(s) (DE, NL)	CAS-No.: 90-30-2 EC-No.: 201-983-0	< 0.1	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-	< 0.1	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-	< 0.1	Not classified
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, HR, NL, PL, CH); substance with a Community workplace exposure limit	EC-No.: 920-901-0 REACH-no: 01-2119456810- 40	< 0.1	Asp. Tox. 1, H304
diphenylamine substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, IE, IT, LT, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 122-39-4 EC-No.: 204-539-4 EC Index-No.: 612-026-00-5 REACH-no: 01-2119488966- 13	< 0.1	Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-naphtol substance with national workplace exposure limit(s) (LT, LV, RO)	CAS-No.: 90-15-3 EC-No.: 201-969-4 EC Index-No.: 604-029-00-5	< 0.1	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
N-Phenyl-1-naphthylamin	CAS-No.: 90-30-2 EC-No.: 201-983-0	(10 ≤ C < 100) STOT RE 2, H373	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	EC-No.: 920-901-0 REACH-no: 01-2119456810- 40	(1 ≤ C < 100) EUH066	

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Exercise caution when fighting any chemical fire. Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid spilling the product, as this might cause falls.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Ensure good ventilation of the work station. Wear

personal protective equipment.

Handling temperature : $\leq 40 \, ^{\circ}\text{C}$

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.

Storage conditions : Store in a well-ventilated place. Keep cool.

Storage temperature : ≤ 40 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Keep only in original container. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA 5 mg/m³		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1] 5 mg/m³		
Hydrocarbons, C10-C13, aromatics, <1% naphthalene		
EU - Indicative Occupational Exposure Limit (IOEL)		
OEL TWA 5 mg/m³		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10-C13, aromatics, <1% naphthalene		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³	
WEL STEL (OEL STEL)	10 mg/m³	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA [ppm]	1200 ppm	
diphenylamine (122-39-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	10 mg/m³	
IOEL STEL	20 mg/m³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	10 mg/m³	
WEL STEL (OEL STEL)	20 mg/m³	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

Personal protective equipment symbol(s):







Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection				
Туре	Field of application	Characteristics	Standard	
Safety glasses	Droplet	clear	EN 166	

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Yellow-brown. Odour Not available Odour threshold : Not available : Not applicable Melting point Freezing point : -15 °C (ASTM D7346) Boiling point : Not available Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available

Flash point : > 201 °C (ASTM D92)

Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available

Viscosity, kinematic : 142 mm²/s @ 40°C (ASTM D7042)

Solubility : insoluble in water.

Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : Not available

Vapour pressure at 50°C : Not available

Density : 892 kg/m³ @ 15°C (ASTM D4052)

Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral (rat) > 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test		
> 2000 mg/kg 402 Acute Dermal Toxicity Test		
> 5000 mg/l/4h		
LC50 inhalation (rat) (Dust/Mist - mg/l/4h) > 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test		

Residual oils (petroleum), solvent-dewaxed (64742-62-7)	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rat)	> 2000 mg/kg

` '	~ ~	
Hydrocarbons, C10-C13, aromatics, <1% naphthalene		
LD50 oral (rat) > 6318 mg/kg OECD TG 401		
LD50 dermal (rat)	> 2000 mg/kg OECD TG 402	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 4.778 mg/l/4h OECD TG 403	
N-Phenyl-1-naphthylamin (90-30-2)		
LD50 oral (rat) 1625 mg/kg Animal: rat. Animal sex: male. 95% CL: 1201 - 2197		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

N-Phenyl-1-naphthylamin (90-30-2)		
LD50 dermal (rabbit)	> 5000 mg/kg	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test	
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test	
Lubricating oils (petroleum), C15-30, hydrotre	eated neutral oil-based (72623-86-0)	
LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test	
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test	
Hydrocarbons, C11-C13, isoalkanes, <2% aro	matics	
LD50 oral (rat)	> 5000 mg/kg	
LD50 dermal (rabbit)	> 5000 mg/kg	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5 mg/l/4h	
diphenylamine (122-39-4)		
LD50 oral (rat)	> 800 mg/kg	
LD50 dermal (rabbit)	> 5000 mg/kg	
1-naphtol (90-15-3)		
LD50 oral (rat)	1870 mg/kg	
LD50 dermal (rabbit)	880 mg/kg	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 97 mg/l/4h	
Skin corrosion/irritation :	Not classified	
Serious eye damage/irritation : Respiratory or skin sensitisation :	Not classified Not classified	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified	
Reproductive toxicity :	Not classified	
N-Phenyl-1-naphthylamin (90-30-2)		
NOAEL (animal/male, F0/P)	< 40 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 83-4 (Reproduction and Fertility Effects), Guideline: EU Method B.35 (Two-Generation Reproduction Toxicity Test)	
NOAEL (animal/female, F0/P)	< 46 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPP 83-4 (Reproduction and Fertility Effects), Guideline: EU Method B.35 (Two-Generation Reproduction Toxicity Test)	
STOT-single exposure :	Not classified	
1-naphtol (90-15-3)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure :	Not classified	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408	
Hydrocarbons, C10-C13, aromatics, <1% naphthalene		
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight OECD Guideline 408	
·		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

NOAEL (subchronic, oral, animal/male, 90 days) NPhenyl-1-naphthylamin (90-30-2) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) LOAEL (oral, rat, 90 days) (25 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight Aspiration hazard 1 Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 425 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 4 25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 1.25 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics Viscosity, kinematic 1.77 mm²/s 40°C	Hydrocarbons, C10-C13, aromatics, <1% naphthalene				
STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Distillates (petroleum), hydrotreated light paraffinic (64742-55-3) LOAEL (oral, rat. 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat. 90 days) 125 mg/kg bodyweight Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 4.25 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	NOAEL (subchronic, oral, animal/male, 90 days) 300 mg/kg bodyweight				
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight Aspiration hazard: Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 - 108) mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 4.25 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 - 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	N-Phenyl-1-naphthylamin (90-30-2)				
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 - 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 2.0.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 - 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics					
(Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)			
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight Aspiration hazard: Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic: 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic: 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic: 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic: 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic: 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neaver animalics animalic	LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OEC				
Hydrocarbons, C11-C13, Isoalkanes, <2% aromatics NOAEL (subchronic, oral, animal/male, 90 days) 1000 mg/kg bodyweight diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) 130 mg/kg bodyweight Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Lubricating oils (petroleum), C15-30, hydrotre	ated neutral oil-based (72623-86-0)			
NOAEL (subchronic, oral, animal/male, 90 days) diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) Aspiration hazard 130 mg/kg bodyweight Aspiration hazard Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight			
diphenylamine (122-39-4) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Hydrocarbons, C11-C13, isoalkanes, <2% around	matics			
STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. 1-naphtol (90-15-3)	NOAEL (subchronic, oral, animal/male, 90 days)	1000 mg/kg bodyweight			
1-naphtol (90-15-3) NOAEL (subchronic, oral, animal/male, 90 days) Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	diphenylamine (122-39-4)				
NOAEL (subchronic, oral, animal/male, 90 days) Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 - 108) mm²/s @ 40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @ 40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @ 40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 - 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.			
Aspiration hazard : Not classified 44880 - INDUSTRIAL SYSTEM OIL CL 150 Viscosity, kinematic 142 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	1-naphtol (90-15-3)				
Viscosity, kinematic Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	NOAEL (subchronic, oral, animal/male, 90 days)	130 mg/kg bodyweight			
Viscosity, kinematic Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard :	Not classified			
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 98 (98 – 108) mm²/s @40°C Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	44880 - INDUSTRIAL SYSTEM OIL CL 150				
Viscosity, kinematic Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Viscosity, kinematic	142 mm²/s @ 40°C (ASTM D7042)			
Residual oils (petroleum), solvent-dewaxed (64742-62-7) Viscosity, kinematic 490 mm²/s @40°C Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)			
Viscosity, kinematic Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Viscosity, kinematic	98 (98 – 108) mm²/s @40°C			
Hydrocarbons, C10-C13, aromatics, <1% naphthalene Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Residual oils (petroleum), solvent-dewaxed (6	4742-62-7)			
Viscosity, kinematic 4.25 mm²/s Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Viscosity, kinematic	490 mm²/s @40°C			
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Hydrocarbons, C10-C13, aromatics, <1% naph	nthalene			
Viscosity, kinematic < 20.5 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Viscosity, kinematic	4.25 mm²/s			
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)				
Viscosity, kinematic 1.99 – 847 mm²/s 40°C Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Viscosity, kinematic	< 20.5 mm²/s @40°C			
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)				
	Viscosity, kinematic	1.99 – 847 mm²/s 40°C			
Viscosity, kinematic 1.77 mm²/s	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics				
	Viscosity, kinematic	1.77 mm²/s			

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term : Not classified

(acute)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long–term : Harmful to aquatic life with long lasting effects. (chronic)

(chronic)			
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
LC50 - Fish [1]	> 100 mg/l Pimephales promelas		
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna		
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitat		
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)		
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)		
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)		
Hydrocarbons, C10-C13, aromatics, <1% naph	nthalene		
LC50 - Fish [1]	3.6 mg/l Oncorhynchus mykiss (OECD 203)		
EC50 - Crustacea [1]	1.1 mg/l OECD 202		
ErC50 algae	3.8 mg/l 72h (Pseudokirchneriella subcapitata, OECD 201)		
NOEC chronic fish	0.103 mg/l 28 d (PETROTOX QSAR)		
NOEC chronic crustacea	0.179 mg/l 21 d (Daphnia magna, OECD 211)		
NOEC chronic algae	0.179 mg/l 72h (Pseudokirchneriella subcapitata, OECD 201)		
N-Phenyl-1-naphthylamin (90-30-2)			
LC50 - Fish [1]	0.44 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)		
EC50 - Crustacea [1]	0.3 mg/l Daphnia magna		
EC50 96h - Algae [1]	0.93 mg/l Pseudokirchneriella subcapitata		
NOEC chronic crustacea	0.032 mg/l Daphnia magna (21d)		
NOEC chronic algae 0.032 mg/l Daphnia magna (21d)			
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)		
LC50 - Fish [1]	> 100 mg/l Pimephales promelas		
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna		
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitat		
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)		
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)		
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)		
Lubricating oils (petroleum), C15-30, hydrotre	ated neutral oil-based (72623-86-0)		
LC50 - Fish [1]	> 100 mg/l Pimephales promelas		
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna		
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)		
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)		
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)		
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			
LC50 - Fish [1]	> 1000 mg/l Oncorhynchus mykiss		
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna		
EC50 72h - Algae [1]	> 1000 mg/l Raphidocelis subcapitata		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			
NOEC chronic algae 100 mg/l Raphidocelis subcapitata (72h)			
diphenylamine (122-39-4)			
LC50 - Fish [1]	3.79 mg/l Pimephales promelas		
EC50 - Crustacea [1]	2 mg/l Daphnia magna (OECD 202)		
EC50 72h - Algae [1]	2.17 mg/l Desmodesmus subspicatus (OECD 201)		
NOEC chronic fish	0.625 mg/l Oryzias latipes (21d)		
NOEC chronic crustacea	0.125 mg/l Daphnia magna (OECD Test Guideline 202) (21d)		
NOEC chronic algae 0.027 mg/l Pseudokirchnerella subcapitata (72h)			
1-naphtol (90-15-3)			
LC50 - Fish [1]	0.33 mg/l M. cavasius		
EC50 - Crustacea [1] 2.51 mg/l Daphnia magna			
EC50 72h - Algae [1]	> 2.18 mg/l Pseudokirchneriella subcapitata		
NOEC chronic crustacea	0.25 mg/l Daphnia magna (21d)		
NOEC chronic algae	> 2.18 mg/l Pseudokirchneriella subcapitata (72h)		

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
Not readily biodegradable.			
31 % OECD TG 301 F (28d)			
nthalene			
Readily biodegradable.			
70 % 28d OECD 301F			
Not readily biodegradable.			
0 % 28d			
affinic (64742-55-8)			
31 % OECD TG 301 F (28d)			
ated neutral oil-based (72623-86-0)			
Not readily biodegradable.			
31 % 28 d OECD 301F			
matics			
31.3 % 28 d Richtlijn test OECD 301F			
diphenylamine (122-39-4)			
26 % OECD TG 301 D (28d)			
77.8 % OECD 301B (29d)			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic (647)	4742-54-7)
--	------------

Partition coefficient n-octanol/water (Log Pow) 3.9 – 6

Residual oils (petroleum), solvent-dewaxed (64742-62-7)

Partition coefficient n-octanol/water (Log Pow) > 3

Hydrocarbons, C10-C13, aromatics, <1% naphthalene

Bioconcentration factor (BCF REACH)	5780
Partition coefficient n-octanol/water (Log Pow)	6.5

N-Phenyl-1-naphthylamin (90-30-2)

Bioconcentration factor (BCF REACH)	
Partition coefficient n-octanol/water (Log Pow)	4.28

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Partition coefficient n-octanol/water (Log Pow) > 6

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics

Bioconcentration factor (BCF REACH) 2500

diphenylamine (122-39-4)

Bioconcentration factor (BCF REACH)		
Partition coefficient n-octanol/water (Log Kow)	3.4	

1-naphtol (90-15-3)

Partition coefficient n-octanol/water (Log Pow)

2.85

12.4. Mobility in soil

Hydrocarbons, C10-C13, aromatics, <1% naphthalene

Organic Carbon Normalized Adsorption Coefficient	3
(Log Koc)	

3.11 @ 20°C

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Ecology - soil Adsorbs into the soil.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

European List of Waste (LoW, EC 2000/532) : 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

09/01/2024 (Revision date) GB - en 12/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID number					
Not regulated for transport					
14.2. UN proper shipping	g name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard c	lass(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental haz	ards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No	
No supplementary information	n available	1		1	

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Diphenylamine (122-39-4)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes				
Section Changed item		Change	Comments	
	Supersedes	Modified		
	Revision date	Modified		
	Flammability (solid, gas)	Added		
1.2	Function or use category	Modified		
1.2	Main use category	Modified		
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified		
2.1	Adverse physicochemical, human health and environmental effects	Added		
2.2	Precautionary statements (CLP)	Modified		
4.1	First-aid measures after skin contact	Added		
4.1	First-aid measures after inhalation	Added		
4.1	First-aid measures after ingestion	Added		
4.1	First-aid measures after eye contact	Added		
4.3	Other medical advice or treatment	Added		
5.1	Suitable extinguishing media	Added		
5.2	Hazardous decomposition products in case of fire	Added		
5.3	Protection during firefighting	Added		
6.1	General measures	Added		
6.1	Protective equipment	Added		
6.1	Emergency procedures	Added		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes				
Section Changed item		Change	Comments	
6.2	Environmental precautions	Added		
6.3	Methods for cleaning up	Added		
6.3	Other information	Added		
6.4	Reference to other sections (8, 13)	Added		
7.1	Precautions for safe handling	Added		
7.1	Hygiene measures	Added		
7.2	Storage conditions	Added		
8.2	Environmental exposure controls	Added		
8.2	Respiratory protection	Added		
8.2	Personal protective equipment	Modified		
8.2	Hand protection	Added		
8.2	Eye protection	Added		
8.2	Appropriate engineering controls	Added		
8.2	Skin and body protection	Added		
9.1	Colour	Added		
9.1	Density	Modified		
9.1	Viscosity, kinematic	Modified		
10.1	Reactivity	Added		
10.2	Chemical stability	Added		
10.3	Possibility of hazardous reactions	Added		
10.4	Conditions to avoid	Added		
10.5	Incompatible materials	Added		
10.6	Hazardous decomposition products	Added		
12.1	Ecology - general	Added		
13.1	European List of Waste (LoW, EC 2000/532)	Added		
13.1	Waste treatment methods	Added		
15.2	Chemical safety assessment	Added		
16	Abbreviations and acronyms	Added		

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acr	Abbreviations and acronyms:		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H331	Toxic if inhaled.	
H335	May cause respiratory irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.