



RACING OIL

10W-60

Product Description:

RACING OIL 10W-60 is a high performance fully synthetic motor oil of exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fueled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.

RACING OIL 10W-60 is based on high quality 100% synthetic Poly Alpha Olefin (PAO) in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

RACING OIL 10W-60 exceeds the following performance criteria:

API SQ

ACEA A3/B4

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-60
Density@15°C	kg/m ³	ASTM D4052	846.3
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	154.0
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	23.9
Viscosity Index		ASTM D2270	187
HTHS viscosity @150°C	mPa.s	ASTM D4683	6.3
Viscosity CCS @-25°C, max	cP	ASTM D5293	5200
MRV @ -30°C	mPa.s	ASTM D4684	18330
Flash Point COC	°C	ASTM D92	238
Noack	%	ASTM D5800	8.1
Pour Point	°C	ASTM D7346	-54
Total Base Number	mgKOH/g	ASTM D2896	12.3
Sulphated Ash	%Wt	ASTM D874	1.09



Product Nr: 42010

Date Superseded: 27-11-2024

Date Issued: 12-12-2025

Revision nr: 10