



MOTOR OIL SL 10W-40

Product Description:

MOTOR OIL SL 10W-40 is an universal high performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbo-charger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR Oil SL 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.

MOTOR OIL SL 10W-40 meets the following performance criteria:

**Approved
Meets**

**MB-Approval 229.1
ACEA A3/B3 API SL/CF
VW 501.01/505.00**

BMW LL-01 > until 2019



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	859
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	159
Viscosity CCS @-25°C, max	cP	ASTM D5293	5260
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	%Wt	ASTM D874	0.95

Product Nr: 42060

Date Superseded: 18-05-2018

Date Issued: 10-12-2019

Revision nr: 05