



MOTOR OIL SYNTHETIC 0W-20

Product Description:

MOTOR OIL SYNTHETIC 0W-20 is high performance fuel conserving engine oil based on 100% synthetic technology for all gasoline engines in passenger cars and light vans.

MOTOR OIL SYNTHETIC 0W-20 is specially designed for the lubricating of the latest generation vehicles like hybrid (Toyota, Honda, Suzuki, etc.) and ECO models which require a SAE 0W-20 and running on gasoline and/or ethanol-containing fuels up to E85.

MOTOR OIL SYNTHETIC 0W-20 is based on synthetic base oil in combination with a special additive package to obtain the following properties.

- Excellent thermal and oxidation stability.
- Excellent cold temperature properties for a smooth cold start.
- Very good dispersant and detergent properties.
- Fuel saving properties due to low friction properties
- Very good antifoam, antiwear and anticorrosion properties.
- Long oil change interval possible.

MOTOR OIL SYNTHETIC 0W-20 Suitable for use where the following specifications are required:

API SQ **API SP** **API SN + RC** **ILSAC GF-7A**
Dexos™1 Gen 3 **Ford WSS-M2C962-A1** **GM 4718M** **Chrysler MS-6395**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-20
Density@15°C	kg/m ³	ASTM D4052	845.9
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	41.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	8.0
Viscosity Index		ASTM D2270	167
Viscosity CCS @-35°C, max	cP	ASTM D5293	5440
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	8.1
Sulphated Ash	%Wt	ASTM D874	0.86

Product Nr: 42150
Date Superseded: 7-10-2025

Date Issued: 21-5-2026
Revision nr: 10