



MOTOR OIL SYNTHETIC 0W-30

Product Description:

MOTOR OIL SYNTHETIC 0W-30 is a high performance fully synthetic motor oil for gasoline- and diesel engines of modern passenger cars and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SYNTHETIC 0W-30 is formulated with high quality 100% synthetic base oil (Poly Alpha Olefin (PAO)) in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

MOTOR OIL SYNTHETIC 0W-30 meets the following performance criteria:

Approved: VCC 95200356

Meets: API SL ACEA A3/B4-16
VW 502.00/505.00 MB 229.3/229.5
Renault RN 0700/0710



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density@15°C	kg/m ³	ASTM D4052	844
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.4
Viscosity Index		ASTM D2270	180
Viscosity CCS @-35°C, max	cP	ASTM D5293	5720
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-50
Total Base Number	mgKOH/g	ASTM D2896	10.1
Sulphated Ash	%Wt	ASTM D874	1.51

Product Nr: 42190
Date Superseded: 18-01-2021

Date Issued: 31-5-2021
Revision nr: 07