



ENGINE OIL HDX 20W-50

Product Description:

ENGINE OIL HDX 20W-50 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

ENGINE OIL HDX 20W-50 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

ENGINE OIL HDX 20W-50 meets the following performance criteria:

API CI-4
MAN M 3275

API SL
Volvo VDS-3

ACEA E7
CAT ECF-1a

MB 228.3/228.1



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density@15°C	kg/m ³	ASTM D4052	884
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	141
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	17.8
Viscosity Index		ASTM D2270	140
Viscosity CCS @-15°C, max	cP	ASTM D2270	4390
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	11.3
Sulphated Ash	%Wt	ASTM D874	1.5

Product Nr: 42480

Date Superseded: 01-05-2018

Date Issued: 11-12-2019

Revision nr: 08