



ENGINE OIL SUPER UHPD 10W-40

Product Description:

ENGINE OIL SUPER UHPD 10W-40 is a high performance fully synthetic engine oil to be used in diesel engines in light- and heavy commercial vehicles with or without turbocharger. **ENGINE OIL SUPER UHPD 10W-40** is designed for use in Euro-II, Euro-III and EURO-IV emission requirements and engines equipped with EGR and/or SCR exhaust after treatment system. **ENGINE OIL SUPER UHPD 10W-40** may not be used in diesel engines equipped with a Diesel Particulate Filter (DPF). Suited for Scania engines which require a LDF-3 performance oil

ENGINE OIL SUPER UHPD 10W-40 is based on high performance synthetic base oil in combination with especially selected additive technology to ensure the following properties.

- Excellent thermal and oxidation stability.
- Excellent protection against forming of "Bore Polishing".
- Suitable for Low emission engine equipped with EGR and SCR technology
- Excellent protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Extended oil drain interval possible

ENGINE OIL SUPER UHPD 10W-40 meets the following performance criteria:

ACEA E4/E7
MTU Type 3
Mack EO-N
CES 20072

API CF
Deutz DQC III-10
Scania LDF-2/ LDF-3
Renault RVI RD-2 / RXD

MB 228.5

Volvo VDS-3

MAN M3277

Renault RVI RLD-2

DAF extended drain



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	867
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	89.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	154
Viscosity CCS @-25°C, max	cP	ASTM D5293	6400
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	16.1
Sulphated Ash	%Wt	ASTM D874	1.85

Product Nr: 42670

Date Superseded: 13-03-2018

Date Issued: 12-12-2019

Revision nr: 03