



# AUTOGEAR OIL MP 85W-90

## Product Description:

**AUTOGEAR OIL MP 85W-90** is an universal high performance mineral multi-purpose gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-90 GL-5 is been required.

**AUTOGEAR OIL MP 85W-90** is based on high quality mineral base oil in combination with a special additive package to ensure the following properties:

- Good thermo-oxidative stability.
- Good load bearing characteristics.
- Effective rust and corrosion protection.
- High low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.

**AUTOGEAR OIL MP 85W-90** meets the following performance criteria:

<b>API GL-5</b>	<b>MIL-L-2105D</b>	<b>MAN 342 M1/M2</b>	<b>MB 235.6</b>
<b>VOLVO 97310</b>	<b>VOLVO 97316</b>	<b>SAE J2360</b>	<b>Meritor 0-76-D</b>
<b>MACK GO-J</b>	<b>Scania STO 1.0</b>	<b>ZF TE-ML05A/07A/08/12M/16D/17B/19B/21A</b>	



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W-90
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	885
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	167
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	16.3
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	< 150000
Viscosity Index		ASTM D2270	102
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27

**Product Nr:** 43070

**Date Superseded:** 08-02-2018

**Date Issued:** 13-12-2019

**Revision nr:** 03