



AUTOGEAR OIL TX

75W-80

Product Description:

AUTOGEAR OIL TX 75W-80 is a high quality fuel saving synthetic thermally stable long life gear lubricant designed for passenger- and commercial vehicles using manual transmissions fitted with different synchronizers including latest ones based on carbon.

AUTOGEAR OIL TX 75W-80 is based on high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo and oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including latest carbon.
- Good frictional properties provide improved fuel economy and smoother shift ability.

AUTOGEAR OIL TX 75W-80 exceeds the following performance criteria.:

Exceeds:	API GL-4	MAN 341 Z4	MAN 341 E3
	IVECO	Volvo 97305	DAF
	Eaton Europe	RENAULT B0032/2 Annex 3	
	ZF TE-ML 01L, 02L, 08, 13, 16K, 24A		



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	75W-80
Density@15°C	kg/m ³	ASTM D4052	855.6
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	56.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.7
Brookfield Viscosity @-40°C	cP	ASTM D2983	100000
Viscosity Index		ASTM D2270	157
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42

Product Nr: 43330

Date Superseded: 4-4-2025

Date Issued: 26-11-2025

Revision nr: 10