



MOTOR OIL SEMI-SYNTH 5W-30

Product Description:

MOTOR OIL SEMI-SYNTH 5W-30 is an universal high performance fuel saving oil based on semi-synthetic technology for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SEMI-SYNTH 5W-30 is formulated with high quality mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SEMI-SYNTH 5W-30 Suitable for use where the following specifications are required::

API SP + RC

ILSAC GF-6A



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	56.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10.5
Viscosity Index		ASTM D2270	174
Viscosity CCS @-30°C	cP	ASTM D5293	3210
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45
Total Base Number	mgKOH/g	ASTM D2896	8.2

Product Nr: 45210

Date Superseded: 3-12-2024

Date Issued: 10-3-2026

Revision nr: 05