



COMPRESSOR OIL

VDL 32

Product Description:

COMPRESSOR OIL VDL 32 is a high performance ash less air compressor oil specially designed to meet the stringent requirements of major compressor manufacturers. **COMPRESSOR OIL VDL 32** is suited for reciprocating air-, rotary screw and vane compressors. Also used in circulating oil systems, plain and rolling element bearings, lightly loaded Gear sets, etc

COMPRESSOR OIL VDL 32 is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Improved equipment reliability, availability and efficiency.
- Low ash and carbon forming tendency ensures improved valve performance.
- Reduced potential for fires and explosions in the discharge systems.
- Exceptional wear and rust protection.
- Superior demulsibility reduces oil carryover and corrosion, maintains lubrication efficiency.
- Reduces sludge formation and improves life of coalesces.

COMPRESSOR OIL VDL 32 meets the following performance criteria:

DIN 51506 VBL/VCL/VDL

ISO 6743 DAA/DAB/DAG/DAH

DIN 51503-1

Property	Unit	Test Method	Typical Value
ISO VG Class			32
Density @15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	33.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.0
Viscosity Index		ASTM D2270	122
Flash Point COC	°C	ASTM D92	>190
Pour Point	°C	ASTM D7346	-33
FZG A/8, 3/90°C		DIN 51354-2	12
Demulsibility @54°C, max	min	DIN 51999	30

Product Nr: 43790

Date Superseded: 18-6-2021

Date Issued: 30-9-2021

Revision nr: 04

