



MOTOR CYCLE OIL 4T 25W-60

Product Description:

MOTOR CYCLE OIL 4T 25W-60 is a high performance mineral engine oil especially developed for use in air-, oil-, and water-cooled 4-stroke motorcycles to provide excellent protection towards engine, gearbox and wet clutches and ensures the highest possible reliability even under the most severe operation conditions.

MOTOR CYCLE OIL 4T 25W-60 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Controlled frictional properties eliminate clutch slippage, effectively improving the driveability of the vehicle.

MOTOR CYCLE OIL 4T 25W-60 exceeds the following performance criteria:

API SL JASO MA-2



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	25W-60
Density@15°C	kg/m ³	ASTM D4052	895
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	244
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	22.9
Viscosity Index		ASTM D2270	116
Viscosity CCS @-10°C, max	cP	ASTM D2270	13000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-21
Total Base Number	mgKOH/g	ASTM D2896	5.9

Product Nr: 45220

Date Superseded: 08-02-2018

Date Issued: 12-12-2019

Revision nr: 01