



ENGINE OIL SPECIAL UHPD 10W-40

Product Description:

ENGINE OIL SPECIAL UHPD 10W-40 is a fuel conserving super high performance “MID SAPS” oil, designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and running on low sulphur diesel fuel (max. 50 ppm). **ENGINE OIL SPECIAL UHPD 10W-40** is formulated for use in Euro 5 and Euro 6 engines equipped with Diesel Particulate Filter (DPF). This product is also suitable for vehicles equipped with EGR and/or SCR after treatment system.

ENGINE OIL SPECIAL UHPD 10W-40 is formulated on high refined 100% synthetic base stock in combination with an special additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against “Bore Polishing”.
- Extended drain intervals up to 150.000 km.
- Suitable for engines equipped with a Diesel Particulate Filter (DPF).
- Fuel conserving.

ENGINE OIL SPECIAL UHPD 10W-40 meets the following performance criteria:

Approved: Volvo VDS-4.5

Meets: ACEA E4/E6/E7/E9

MTU Type 3.1/2.1

Scania Low-Ash

Deutz DQC IV-10-LA

CAT ECF-3

Mack EOS-4.5

API CJ-4

MAN M3477/3575/3271-1

Detroit 93K218

Mack EO-N Premium Plus

Renault VI RLD-3

MB 228.31/228.51

Cummins CES 20081

JASO DH-2

Renault VI RLD-2



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	862
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	94.4
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.2
Viscosity Index		ASTM D2270	155
Viscosity CCS @-25°C, max	cP	ASTM D5293	6800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	12.7
Sulphated Ash	%Wt	ASTM D874	0.98

Product Nr: 42790

Date Superseded: 11-12-2019

Date Issued: 08-01-2021

Revision nr: 06