



# HYDRAULIC OIL

## HV 32

### Product Description:

**HYDRAULIC OIL HV 32** is an universal HVI mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

**HYDRAULIC OIL HV 32** is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Excellent stability against oxidation.
- High Viscosity Index.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- Very good thermal stability.

**HYDRAULIC OIL HV 32** exceeds the following performance criteria:

**DIN 51524-3 HVLP**  
**AFNOR NF E 48-603 HV**  
**Eaton Vickers M-2950-S / I-286**

**ISO 11158 HV**  
**Cincinnati P-68**

**ASTM D6158 HV**  
**Sauer Danfoss 520L0463**



Property	Unit	Test Method	Typical Value
ISO Grade		ISO 3448	32
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	861
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	33.2
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	6.9
Viscosity Index		ASTM D2270	174
Flash Point COC	°C	ASTM D92	>190
Pour Point	°C	ASTM D7346	-45
Air Release Value @50°C	Minutes	ASTM D3427	Pass
Demulsibility @54°C	Minutes	ASTM D1401	Pass

**Product Nr:** 43580  
**Date Superseded:** 10-03-2022

**Date Issued:** 31-10-2022  
**Revision nr:** 07