



EPS GREASE

NLGI 0

Product Description:

EPS GREASE NLGI 0 is a multifunctional EP grease enhanced by the plastic deformation of its micro additives and formulated for lubrication under hard mechanical conditions and high rates of lubrication frequency.

EPS GREASE NLGI 0 can be used for the following applications:

- types of bearings which work with strong loads, vibrations or in a humid environment.
- On smooth bearings, including yellow alloys, which work with heavy loads or partial rotation with wear and tear due to abrasion.
- To protect the development of rough or accelerated wear and tear of bearings and grooves in Cardan type transmissions and grooved joints with high torques.
- Lubrication in rolling mills.
- NLGI class 0 is best suited for the centralized lubrication of trucks, cars, etc.

EPS GREASE NLGI 0 has the following benefits:

- Great wear and tear reduction, anticorrosive, antioxidant and antirust properties
- High adherence and lubricity.
- Excellent pump-ability for use with gun and centralized greasing.

Temp Range: Continuous operation: -30°C to + 120°C. Short periods maximum +135°C
Maximum usage temperatures recommended for treads depending on the speed factor.

EPS GREASE NLGI 0 exceeds the following performance criteria.:

KP0G-30

L-XBCEB-2

Property	Unit	Test Method	Typical Value
NLGI Grade		ASTM D217	0
Thickener			Lithium
Base Oil Nature			Mineral
Base Oil Viscosity	cSt	ASTM D445	100
Color		Visual	Amber
Dropping Point	°C	ASTM D2265	>160
Worked penetration, 25°C / 60		ASTM D217	355-385
Penetration loss: After 105		ASTM D217	<30
Water Resistance, 3h, 90°C		DIN 51807	1
TIMKEN, LOAD O.K	Lbs	ASTM D2509	>45
4-BALL E.P. test: - Welding load	Kg	ASTM D2783	250
4-BALL WEAR test: - (40	Mm	ASTM D2266	<0.40

Product Nr: 45260

Date Superseded: 25-09-2020

Date Issued: 8-10-2025

Revision nr: 3

