



# MOTOR CYCLE OIL

# SYN 4T

# 15W-50

## Product Description:

**MOTOR CYCLE OIL SYN 4T 15W-50** is a high performance semi synthetic 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air and water-cooled 4-stroke motorcycles.. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

**MOTOR CYCLE OIL SYN 4T 15W-50** is based on high quality synthetic technology Hydrocracked and hydro treated base stocks in combination with a special selected additive package to obtain the following properties.

- Outstanding thermo-oxidative stability.
- Exceptional anti-wear, anti-rust and anti-corrosion properties.
- High friction properties to eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- 

**MOTOR CYCLE OIL SYN 4T 15W-50** meets the following performance criteria:

**API SN JASO MA/MA2**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-50
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	859
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	134
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	19.3
Viscosity Index		ASTM D2270	140
Viscosity CCS @-20°C, max	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-21
Total Base Number	mgKOH/g	ASTM D2896	8.5

**Product Nr:** 42975  
**Date Superseded:-**

**Date Issued:** 2-2-2021  
**Revision nr:** -