



MOTOR OIL SL

15W-40

Product Description:

MOTOR OIL SL 15W-40 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

MOTOR OIL SL 15W-40 is based on high performance mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

MOTOR OIL SL 15W-40 meets the following performance criteria:

ACEA A3/B3

API SN

MB 229.1

VW 501.01/505.00



| Property | Unit | Test Method | Typical Value |
|---------------------------|--------------------|-------------|---------------|
| SAE Grade | | SAE J300 | 15W-40 |
| Density@15°C | kg/m ³ | ASTM D4052 | 858 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 88 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 13.5 |
| Viscosity Index | | ASTM D2270 | 155 |
| HTHS viscosity @150°C | mPa.s | ASTM D4683 | 3.8 |
| Viscosity CCS @-20°C, max | cP | ASTM D5293 | 3100 |
| Flash Point COC | °C | ASTM D92 | 220 |
| Pour Point | °C | ASTM D7346 | -36 |
| Total Base Number | mgKOH/g | ASTM D2896 | 9.1 |

Product Nr: 42080

Date Superseded: 22-09-2021

Date Issued: 11-08-2022

Revision nr: 07