



# MOTOR OIL SF 20W-50

## Product Description:

**MOTOR OIL SF 20W-50** is a multi functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger car and light vans with or without turbo compressor. MOTOR OIL SF 20W-50 is not suited for engines equipped with a Diesel Particulate Filter (DPF).

**MOTOR OIL SF 20W-50** is formulated with special selected base stocks in combination with unique additive package to reach the following properties:

- Stable viscosity index.
- Good protection against rust, corrosion and wear.
- Good dispergency and detergency properties.
- Good antifoam properties.

**MOTOR OIL SF 20W-50** meets the following performance criteria:

## API SF/CD

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	881
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	154
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	18.03
Viscosity Index		ASTM D2270	129
Viscosity CCS @-15°C, max	cP	ASTM D5293	5770
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	5.6
Sulphated Ash	%Wt	ASTM D874	0.66

**Product Nr:** 42140

**Date Superseded:** 15-01-2018

**Date Issued:** 10-12-2019

**Revision nr:** 03

