



MOTOR OIL CT

5W-40

Product Description:

MOTOR OIL CT 5W-40 is a cost effective fuel saving MID SAPS technology and used in light duty vehicles fitted with direct injection, turbocharges and after-treatment systems, gasoline catalytic converter, or diesel particulate filter technology.

MOTOR OIL CT 5W-40 is based on high performance base oils in combination with a specially selected additive technology to ensure the following properties:

- Strong Fuel Economy Performance
- Excellent Engine Durability
- Excellent Engine Compatibility
- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam and corrosion.
- Good low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.



MOTOR OIL CT 5W-40 meets the following performance criteria:

API SP

ACEA C3

MB 229.31

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-40
Density @15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D445	83
Kin. Viscosity @100°C	mm ² /s	ASTM D445	13.8
Viscosity Index		ASTM D2270	171
Viscosity CCS @ -30°C	cP	ASTM D5293	6100
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-36
Total Base Number	mgKOH/g	ASTM D2896	8.1

Product Nr: 42325

Date Superseded: 04-01-2022

Date Issued: 15-03-2022

Revision nr: 02