



MOTOR OIL SYNTHETIC 10W-30

Product Description:

MOTOR OIL SYNTHETIC 10W-30 is a high performance fuel saving engine oil based on synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA A3/B4 specification is required and suitable for all engines which require an MB 229.3 performance specification.

MOTOR Oil SYNTHETIC 10W-30 is based on synthetic technology base oil in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SYNTHETIC 10W-30 meets the following performance criteria:

API SP* **ACEA A3/B4** **MB 229.3**

*exceeds API SP performance, but does not meet phosphorus limit



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-30
Density@15°C	kg/m ³	ASTM D4052	860
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	73.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.9
Viscosity Index		ASTM D2270	158
Viscosity CCS @-25°C,	cP	ASTM D5293	4163
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-37
Total Base Number	mgKOH/g	ASTM D2896	10.2
Sulphated Ash	%Wt	ASTM D874	1.31

Product Nr: 42350
Date Superseded: 19-01-2021

Date Issued: 11-08-2022
Revision nr: 05