



# MOTOR OIL CP 0W-30

## Product Description:

**MOTOR OIL CP 0W-30** is a high performance fuel saving engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ACEA C2 specification is required and suitable for all engines which require an PSA B71 2290 performance specification.

**MOTOR OIL CP 0W-30** is based on high performance 100% synthetic technology oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

**MOTOR OIL CP 0W-30** meets the following performance criteria:

**ACEA C2**      **PSA B71 2290**      **Ford M2C950-A**      **JLR 03.5007**

**Suitable for use:** **Fiat 9.55535-GS1**      **Fiat 9.55535-DS1**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	0W-30
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	845
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	47.5
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.7
Viscosity Index		ASTM D2270	196
Viscosity CCS @-35°C	cP	ASTM D5293	5800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	7.7
Sulphated Ash	%Wt	ASTM D874	0.79

**Product Nr:** 42430

**Date Superseded:** 19-01-2021

**Date Issued:** 28-12-2022

**Revision nr:** 06