



MONO ENGINE OIL CF 10W

Product Description:

MONO ENGINE OIL CF 10W is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

MONO ENGINE OIL CF 10W is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

MONO ENGINE OIL CF 10W is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

MONO ENGINE OIL CF 10W meets the following performance criteria:

API SF/CF **MTU Type 2** **CCMC G2/D1** **MIL-L-46152**

Suitable for use: **API CH-4**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W
Density@15°C	kg/m ³	ASTM D4052	878
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	38
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.2
Viscosity Index		ASTM D2270	107
Viscosity CCS @-25°C	cP	ASTM D5293	5404
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	12.8

Product Nr: 42620

Date Superseded: 23-06-2021

Date Issued: 30-06-2023

Revision nr: 07