



ENGINE OIL HDX EXTRA 15W-40

Product Description:

ENGINE OIL HDX EXTRA 15W-40 is a extra high performance, extra high TBN, universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions in combination with high-sulphur diesel fuels.

ENGINE OIL HDX EXTRA 15W-40 is suitable for use in engine with (EGR and SCR) and without exhaust gas after treatment systems, making the product suitable for engines of Euro-1 up to Euro-5. This product is not suitable for vehicles equipped with DPF filters.

ENGINE OIL HDX EXTRA 15W-40 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Extra protection against high sulphur fuels.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

ENGINE OIL HDX EXTRA 15W-40 meets the following performance criteria:

API CI-4/SL	ACEA E7	Volvo VDS-3	MACK EO-N
MB 228.3	MAN M 3275	Renault RLD-2	Global DHD-1
JASO DH-1	Allison C4	MTU Type 2	Mack EO-M
DAF HP-2	Cummins CES	2077/20078	CAT ECF-2
DDC 93K215			



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m ³	ASTM D4052	871
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	111
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	15.4
Viscosity Index		ASTM D2270	149
Viscosity CCS @-20°C, max	cP	ASTM D5293	5200
Flash Point COC	°C	ASTM D92	>230
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	15.7
Sulphated Ash	%Wt	ASTM D874	1.5

Product Nr: 42630

Date Superseded: 25-01-2018

Date Issued: 12-12-2019

Revision nr: 02