



MONO ENGINE OIL CF

40



Product Description:

MONO ENGINE OIL CF 40 is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

Mono Engine Oil CF 40 is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

MONO ENGINE OIL CF 40 is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

MONO ENGINE OIL CF 40 meets the following performance criteria:

API SF/CF **MTU Type 2** **CCMC G2/D1** **MIL-L-46152**

Suitable for use: **API CH-4**

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	895
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	141
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.0
Viscosity Index		ASTM D2270	96
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-23
Total Base Number	mgKOH/g	ASTM D2896	12.7
Sulphated Ash	%Wt	ASTM D874	1.85

Product Nr: 42680

Date Superseded: 23-04-2021

Date Issued: 30-06-2023

Revision nr: 07