



SNOW MOBILE OIL SYN 2T

Product Description:

SNOW MOBILE OIL SYN 2T is a fully synthetic excellent performance lubricant developed for air & water cooled 2-stroke engines. The special formulation ensures excellent engine protection, cleanliness and low smoke, even under extreme operating conditions.

SNOW MOBILE OIL SYN 2T is based on a high quality fully synthetic base oils in combination with a special selected additive package to obtain the following properties:

- Outstanding protection against piston scuffing and premature wear of engine components.
- Excellent control against engine deposits, exhaust system blocking.
- Extended engine life without power loss.
- Low ash additive technology prevents pre-ignition and spark plug fouling.
- Specially selected synthetic base fluid reduces visible exhaust smoke.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at very low ambient temperatures.

SNOW MOBILE OIL SYN 2T meets the following performance criteria:

API TC
Husqvarna 346

JASO FD

ISO-L-EGD
Husqvarna 372

ROTAX 253



Property	Unit	Test Method	Typical Value
Density@15°C	kg/m ³	ASTM D4052	875
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	50
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.1
Viscosity Index		ASTM D2270	164
Flash Point COC	°C	ASTM D92	>90
Pour Point	°C	ASTM D7346	-54
Total Base Number	mgKOH/g	ASTM D2896	1.6
Sulphated Ash	%Wt	ASTM D78	0.15

Product Nr: 42910

Date Superseded: 29-01-2018

Date Issued: 12-12-2019

Revision nr: 03