## Product Data Sheet

## **2T RACING**

## **Product Description:**

**KART 2T RACING** is a high performance ultimate lubricant based on synthetic ester and castor proven base oil. KART 2T is specially developed for high revving 2-stroke air- and/or water-cooled kart engines which run under severe/ racing conditions.

**KART 2T RACING** is formulated with high quality synthetic ester and castor base stocks in combination with an unique additive technology to achieve the following performance:

- More power and better bearing protection.
- Very high film strength and affinity for hot metal.
- Excellent scuff protection.
- Exceptional Piston Cleanliness.
- Low carbon residue, reduces smoke.

Property	Unit	Test Method	Typical Value
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	939
Kin. Viscosity @40°C	mm²/s	ASTM D7042	150
Kin. Viscosity @100°C	mm²/s	ASTM D7042	18.1
Viscosity Index		ASTM D2270	134
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45

**Product Nr:** 43000 **Date Superseded:** 08-02-2018

**Date Issued:** 13-12-2019 **Revision nr:** 03

77 B.V. | Van Ewijckskade 1C 1761 JA Anna Paulowna, The Netherlands | info@77lubricants.nl



