



ATF DX II

Product Description:

ATF DX II is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

ATF DX II is formulated on high quality re-refined mineral and virgin synthetic base oil in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against corrosion, foam and wear.

ATF DX II meets the following performance criteria:

GM Dexron II-D **GM Type A** **MB 236.9** **Voith H55.6335.xx**
MAN 339 type Z1 **MAN 339 type V1** **ZF TE-ML 03D/04D/14A/17C**



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m ³	ASTM D4052	847
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	35.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.3
Viscosity Index		ASTM D2270	175
Viscosity Brookfield @-40°	cP	ASTM D2983	18.000
Flash Point COC	°C	ASTM D92	172
Pour Point	°C	ASTM D7346	-48

Product Nr: 43200
Date Superseded: 26-01-2021

Date Issued: 10-03-2023
Revision nr: 06