



ATF DX III

Product Description:

ATF DX III is a high quality universal fluid to be used in automatic transmission, torque converters and power steering of passenger car, light vans and commercial vehicles.

ATF DX III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF DX III meets the following performance criteria:

DEXRON III H	Allison C4	MAN 339 V1/Z1	MB 236.9
Voith H55.6335.xx	ZF TE-ML 03D	ZF TE-ML 14A	VOLVO 97341
FORD M	GM D-IID	GM D-IIIG/H	VOLVO 97340



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	36.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.6
Viscosity Index		ASTM D2270	180
Viscosity Brookfield @-40°, max.	cP	ASTM D2983	< 20000
Flash Point COC	°C	ASTM D92	201

Product Nr: 43220
Date Superseded: 21-02-2018

Date Issued: 16-12-2019
Revision nr: 05