



HYDRAULIC OIL

HV ZF 46

Product Description:

HYDRAULIC OIL HV ZF 46 is an universal Zinc free mineral oil with a High Viscosity Index (HVI) for the use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

HYDRAULIC OIL HV ZF 46 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good stability against oxidation.
- High Viscosity Index
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- Very good thermal stability.

HYDRAULIC OIL HV ZF 46 exceeds the following performance criteria:

DIN 51524-3 HVLP **ISO 11158 HV** **ASTM D6158 HV**
AFNOR NF E 48-603 HV **Cincinnati P-70** **Sauer Danfoss 520L0463**
Denison HF-0/HF-1/HF-2 **Bosch Rexroth RE 90 220** **Eaton Vickers M-2950-S / I-286**
General Motors LS-2



| Property | Unit | Test Method | Typical Value |
|-------------------------|--------------------|-------------|---------------|
| ISO Grade | | ISO 3448 | 46 |
| Density@15°C | kg/m ³ | ASTM D4052 | 870 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 46.5 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 8.5 |
| Viscosity Index | | ASTM D2270 | 161 |
| Flash Point COC | °C | ASTM D92 | >200 |
| Pour Point | °C | ASTM D7346 | -42 |
| Air Release Value @50°C | Minutes | ASTM D3427 | Pass |
| Demulsibility @54°C | Minutes | ASTM D1401 | Pass |

Product Nr: 43630
Date Superseded: 18-06-2021

Date Issued: 02-11-2022
Revision nr: 06