



ANTIFREEZE

Product Description:

ANTIFREEZE is a silicate, amine-, nitrites- and phosphates free antifreeze concentrate providing frost and corrosion protection. For the perfect operation of water-cooled internal combustion engines.

ANTIFREEZE may not be used undiluted in a combustion engine.

ANTIFREEZE is based Mono Ethylene Glycol in combination with a powerful additive technology to obtain the following benefits:

- Corrosion protection, also for non-ferro metals.
- Frost protection.
- Boiling protection.
- Seal compatibility.
- Hard water stability.
- Miscibility.

ANTIFREEZE meets the following performance criteria:

British Standard (BS) 6580
SAE J-1034

AFNOR 15-601 **ASTM D3306**
CUNA NC 956-16



Property	Unit	Test Method	Typical Value
Color			Blue
Density @15°C	kg/m ³	ASTM D5931	1.131
Equilibrium Boiling Point	°C	ASTM D1120	155
Reserve Alkalinity (pH 5.5)		ASTM D1121	3.0
Refractive Index, 20°C		ASTM D1218	1.435
Freezing Protection			
33% dilution with water	°C		-17
50% dilution with water	°C		-33

Product Nr: 43940
Date Superseded: 29-05-2018

Date Issued: 23-12-2019
Revision nr: 03