



FORM OIL 135

Product Description:

FORM OIL 135 is a concrete mould oil for the construction of houses, buildings, subways and bridges.

FORM OIL 135 is based on high-grade refined base oils containing non-toxic surface-active compounds and together with the bleeding water from the concrete, it provides a low interfacial surface tension, which gives a smooth surface finish.

FORM OIL 135 is ready to use, and should be applied as thin as possible on the surface.

FORM OIL 135 enables easy removal from the moulds without damaging the concrete and gives a good rust protection of the steel moulds under normal condition. Has good release characteristics and gives no discolouring of the concrete-surface and can be used where limited heated moulds are adapted.

Appliance in a thin layer, by spraying, swabbing or brushing.
Over spill must be removed.



Property	Unit	Test Method	Typical Value
ISO VG Grade			135
Density@15°C	kg/m ³	ASTM D4052	892
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	122.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.1
Viscosity Index		ASTM D2270	100
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-9

Product Nr: 44030

Date Superseded: 07-05-2012

Date Issued: 19-12-2019

Revision nr: 02