



# MARINE CEO 570

## Product Description:

**MARINE CEO 570** is an extra high performance Marine Cylinder Lubricant (MCL) designed for the latest generation technology of low speed crosshead diesel engines operating on wide range of residual fuels having sulphur content in excess of 1.0%  
Feed rates recommended by the manufacturer should be maintained as a minimum. Higher feed rates may be required when running new liners and/or rings.

**MARINE CEO 570** is based on high quality virgin mineral base oils in combination with an unique additive package to ensure the following properties:

- Good acid neutralising capability.
- Superior detergency minimises deposits on critical parts such as pistons, piston rings, ring grooves and cylinder ports.
- Good antiwear properties minimizes piston ring & cylinder wear leading to reduced maintenance costs.
- Good compatibility with all normal seal materials.



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	50
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	932
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	227
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	19.8
Viscosity Index		ASTM D2270	100
Flash Point COC	°C	ASTM D92	>230
Pour Point	°C	ASTM D7346	-12
Total Base Number	mgKOH/g	ASTM D2896	70

**Product Nr:** 44520

**Date Superseded:** 04-06-2012

**Date Issued:** 17-12-2019

**Revision nr:** 02