



INDUSTRIAL SYSTEM OIL CL 68

Product Description:

INDUSTRIAL SYSTEM OIL CL 68 is a good quality multipurpose lubricating oil for use in circulating systems and certain other industrial applications which do not require oils with EP properties.

INDUSTRIAL SYSTEM OIL CL 68 is formulated with special selected virgin mineral base stocks in combination with an unique additive technology to achieve the following performance.

- Long service intervals.
- Excellent protection against rust, wear and foaming.
- Very high demulsibility.
- Good air release properties.

INDUSTRIAL SYSTEM OIL CL 68 exceeds the following performance criteria:

DIN 51517-2 CL

DIN 51524-1 HL

AFNOR NF E 48-603 HL



Property	Unit	Test Method	Typical Value
ISO VG Grade		ISO 3448	68
Density@15°C	kg/m ³	ASTM D4052	883
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	66
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	8.5
Viscosity Index		ASTM D2270	100
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
Demulsibility @54°C	max	ASTM D1401	15

Product Nr: 44920

Date Superseded: 02-05-2012

Date Issued: 19-12-2019

Revision nr: 01