## Product Data Sheet 4-STROKE OUTBOARD 10W-40

## **Product Description:**

**4-STROKE OUTBOARD 10W-40** is a premium 4-stroke engine oil specially designed for the most modern high output gasoline power, water cooled outboard / inboard and personal watercraft engines. It is specially developed to exceed the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W Catalyst Compatible® (Four Cycle-Water specification).

**4-STROKE OUTBOARD 10W-40** is based on a high quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional shear stability.
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment.
- Good Low temperature fluidity assists easy cold start.
- Active cleaning agents provide superior engine cleanliness

4-STROKE OUTBOARD 10W-40 exceeds the following performance criteria:

## NMMA FC-W NMMA FC-W Catalyst Compatible<sup>®</sup> API SM

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	10W-40
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	862
Kin. Viscosity @40°C	mm²/s	ASTM D7042	91
Kin. Viscosity @100°C	mm²/s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	150
Viscosity CCS @-25°C	сР	ASTM D2270	6100
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	7.1

Product Nr: 43281 Date Superseded: - Date Issued: 16-02-2024 Revision nr: -

