



MOTOR OIL SL

10W-40

Product Description:

MOTOR OIL SL 10W-40 is an universal high performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR Oil SL 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.

MOTOR OIL SL 10W-40 exceeds the following performance criteria:

ACEA A3/B3

API SN

MB 229.1

VW 501.01/505.00



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	854.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	161
HTHS viscosity @150°C	mPa.s	ASTM D4683	3.9
Viscosity CCS @-25°C	cP	ASTM D5293	4510
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.5
Sulphated Ash	%Wt	ASTM D874	1.1

Product Nr: 42060**Date Superseded:** 11-08-2022**Date Issued:** 27-11-2024**Revision nr:** 09