



MOTOR OIL SF

20W-50

Product Description:

MOTOR OIL SF 20W-50 is a multi functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger car and light vans with or without turbo compressor. MOTOR OIL SF 20W-50 is not suited for engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SF 20W-50 is formulated with special selected base stocks in combination with unique additive package to reach the following properties:

- Stable viscosity index.
- Good protection against rust, corrosion and wear.
- Good dispersancy and detergency properties.
- Good antifoam properties.

MOTOR OIL SF 20W-50 exceeds the following performance criteria:

API SF/CD

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density@15°C	kg/m ³	ASTM D4052	882.4
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	153.4
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	17.8
Viscosity Index		ASTM D2270	128
Viscosity CCS @-15°C, max	cP	ASTM D5293	6080
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	7.3
Sulphated Ash	%Wt	ASTM D874	0.66



Product Nr: 42140
Date Superseded: 18-1-2021

Date Issued: 27-11-2024
Revision nr: 05