



MOTOR OIL SYNTHETIC 10W-40

Product Description:

MOTOR OIL SYNTHETIC 10W-40 is an universal high performance fuel saving synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL SYNTHETIC 10W-40 is formulated with high quality synthetic base stock in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL SYNTHETIC 10W-40 exceeds the following performance criteria:

Approved MB-Approval 229.3

Exceeds API SP ACEA A3/B4 MB 226.5
RN 0700/0710 VW 501.01/505.00



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	860.1
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	90.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	155
Viscosity CCS @-25°C	cP	ASTM D5293	5980
Flash Point COC	°C	ASTM D92	>215
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	11.3
Sulphated Ash	%Wt	ASTM D874	1.3

Product Nr: 42340
Date Superseded: 11-08-2022

Date Issued: 29-11-2024
Revision nr: 08