



AUTOGEAR OIL MP

80W-140

Product Description:

AUTOGEAR OIL MP 80W-140 is a universal high performance mineral multi-purpose gear oil for use in differentials, axles and some transmissions of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 80W-140 GL-5 is been required. This product is also suitable for applications where a SAE 85W-140 GL-5 is required.

AUTOGEAR OIL MP 80W-140 is based on high quality mineral base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Excellent load bearing characteristics.
- Effective rust and corrosion protection.
- Excellent wear protection
- Exceptional shear stability

AUTOGEAR OIL MP 80W-140 exceeds the following performance criteria:

API GL-5 MIL-L-2105D MIL-L-2105E SAE J2360 Scania STO 1:0
ZF TE-ML 05A/07A/08/12M/16C/16D/21A



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	80W-140
Density@15°C	kg/m ³	ASTM D4052	896.3
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	243.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	26.5
Low-Temperature Brookfield Viscosity @ -26°	cP	ASTM D2983	< 150000
Viscosity Index		ASTM D2270	141
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33

Product Nr: 43090
Date Superseded: 24-6-2021

Date Issued: 24-12-2024
Revision nr: 06