

## INDUSTRIAL SYSTEM OIL

**CL 150** 

## **Product Description:**

**INDUSTRIAL SYSTEM OIL CL 150** is a good quality multipurpose lubricating oil for use in circulating systems and certain other industrial applications which do not require oils with EP properties.

**INDUSTRIAL SYSTEM OIL CL 150** is formulated with special selected virgin mineral base stocks in combination with an unique additive technology to achieve the following performance.

- Long service intervals.
- Excellent protection against rust, wear and foaming.
- Very high demulsibility.
- Good air release properties.

**INDUSTRIAL SYSTEM OIL CL 150** exceeds the following performance criteria:

DIN 51517-2 CL DIN 51524-1 HL AFNOR NF E 48-603 HL

Property	Unit	Test Method	Typical Value
ISO VG Grade		ISO 3448	150
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	891.3
Kin. Viscosity @40°C	mm²/s	ASTM D7042	149.1
Kin. Viscosity @100°C	mm²/s	ASTM D7042	14.5
Viscosity Index		ASTM D2270	96
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-18
Demulsibility @82°C	max	ASTM D1401	10

Product Nr: 44880 Date Issued: 3-1-2025

**Date Superseded:** 19-12-2019 **Revision nr:** 02

