



ENGINE OIL D MX IV

20W-50

Product Description:

ENGINE OIL D MX IV 20W-50 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-1, Euro-2 and Euro-3 engines equipped with EGR and/or SCR.

ENGINE OIL D MX IV 20W-50 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

ENGINE OIL D MX IV 20W-50 exceeds the following performance criteria:

API CH-4
MAN M 3275
MTU Typ 2.0

API SJ
Volvo VDS-3
Cummins CES 20077

MB 228.3/228.1
CAT ECF-1a

Mack EO-M
Deutz DQC-II



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density@15°C	kg/m ³	ASTM D4052	884.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	159.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	18.9
Viscosity Index		ASTM D2270	134
Viscosity CCS @-15°C	cP	ASTM D2270	5580
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	11.3
Sulphated Ash	%Wt	ASTM D874	1.3

Product Nr: 45370
Date Superseded: 16-11-2021

Date Issued: 12-12-2024
Revision nr: 02