



ENGINE OIL VFE

5W-30

Product Description:

ENGINE OIL VFE 5W-30 is a fuel saving MID SAPS, lowered HTHS, super high performance engine oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year.

ENGINE OIL VFE 5W-30 is intended use in specific Euro-6 engines; please consult the owner's manual and/or the 77 oil-finder to check suitability.

ENGINE OIL VFE 5W-30 is formulated on high refined synthetic base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals up to 150.000 km.
- Suitable for engines equipped with a Diesel Particulate Filter (DPF).
- Fuel conserving

ENGINE OIL VFE 5W-30 exceeds the following performance criteria.:

Approved: **Volvo VDS 5** **Mack EOS-5** **Renault VI RLD-5**
 DTFR 15C130

Exceeds: **API FA-4** **ACEA F01** **API SN**
 JASO DH-2 **Cummins CES 20087** **DDC 93K223**
 Ford WSS-M2C214-B1



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	5W-30
Density@15°C	kg/m ³	ASTM D4052	856
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	54.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.8
Viscosity Index		ASTM D2270	167
Viscosity CCS @ -30°C	cP	ASTM D5293	5800
HTHS @150°C	mPa*s	ASTM 4683	3.0
Total Base Number	mgKOH/g	ASTM D2896	9.8
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36

Product Nr: 42542

Date Superseded: 25-03-2025

Date Issued: 27-05-2025

Revision nr: 01