



MOTOR OIL SFP

5W-30

Product Description:

MOTOR OIL SFP 5W-30 is a very high performance fuel saving engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger cars and light vans. Specially designed to meet the requirements of the Stellantis FPW9.55535/03 specification.

MOTOR OIL SFP 5W-30 is formulated with high quality synthetic base stocks in combination with special selected additive technology to achieve the following performance:

- Good thermal and oxidation stability.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Fuel saving properties.
- Excellent detergency and dispersancy properties.

MOTOR OIL SFP 5W-30 exceeds the following performance criteria.:

Exceeds:	ACEA C3	API SQ	Stellantis FPW9.55535/03
	MB 229.52	MB 229.51	Stellantis FPW9.55535/05
	MB 226.52	Renault RN17	PSA B71 2297
	OV 040 1547-G30	OV 040 1547-D30	PSA B71 2290
	GM DEXOS 2	GB 11121	



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	5W-30
Density@15°C	kg/m ³	ASTM D4052	851
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	75.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	160
Viscosity CCS @-30°C	cP	ASTM D5293	6200
Total Base Number	mgKOH/g	ASTM D2896	9.9
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42
Sulphated Ash	%Wt	ASTM D874	0.75

Product Nr: 42438

Date Superseded: 23-5-2025

Date Issued: 14-4-2026

Revision nr: 1