



MOTOR OIL SN

10W-40

Product Description:

MOTOR OIL SN 10W-40 is a premium quality semi synthetic passenger car motor oil, designed to meet the very latest performances of API SQ and ILSAC GF-7A. Recommended for all types of modern vehicles where SAE 10W-40 viscosity is recommended.

MOTOR OIL SN 10W-40 is based on semi synthetic base oil in combination with a special additive package to obtain the following properties.

- Excellent thermal and oxidation stability.
- Excellent cold temperature properties for a smooth cold start.
- Very good dispersant and detergent properties.
- Fuel saving properties due to low friction properties
- Very good antifoam, antiwear and anticorrosion properties.
- Long oil change interval possible.

MOTOR OIL SN 10W-40 exceeds the following performance criteria:

API SQ**API SP****API SN + RC****ILSAC GF-7A**

| Property | Unit | Test Method | Typical Value |
|-----------------------|--------------------|-------------|---------------|
| SAE Grade | | SAE J300 | 10W-40 |
| Density@15°C | kg/m ³ | ASTM D4052 | 852.6 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 85.4 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 13.9 |
| Viscosity Index | | ASTM D2270 | 168 |
| HTHS viscosity @150°C | mPa.s | ASTM D4683 | 3.6 |
| Viscosity CCS @-30°C | cP | ASTM D5293 | 3250 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -42 |
| Total Base Number | mgKOH/g | ASTM D2896 | 7.5 |

Product Nr: 42055**Date Superseded:** 4-12-2024**Date Issued:** 7-10-2025**Revision nr:** 03