



MOTOR OIL MP

5W-30

Product Description:

MOTOR OIL MP 5W-30 is an high performance engine oil based on 100% synthetic technology for use especially in Mercedes-Benz, Renault and VW as well as in other gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

MOTOR OIL MP 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

MOTOR OIL MP 5W-30 exceeds the following performance criteria:

API SP*	ACEA A3/B4	MB 226.5	MB 229.3
MB 229.5	Renault 0700/0710	GM-LL-025-A	GM-LL-025-B
VW 502.00/505.00			

*exceeds API SP performance, but does not meet phosphorus limit



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m ³	ASTM D4052	850.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	68.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.7
Viscosity Index		ASTM D2270	167
Viscosity CCS @-30°C	cP	ASTM D5293	5760
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	11.4
Sulphated Ash	%Wt	ASTM D874	1.3

Product Nr: 42465
Date Superseded: 11-08-2022

Date Issued: 3-12-2024
Revision nr: 2